Revision: 23.01.2023

Start

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.01.2023

*Version number 6 (replaces version 5)* 

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Fix Solvent Aerosol
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the mixture Solvents
- · Uses advised against No further relevant information available.
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Dentsply DeTrey GmbH

De-Trey-Str. 1 D-78467 Konstanz **GERMANY** 

Tel.: +49-(0)7531-583-0 Fax: +49-(0)7531-583-104

email: KonstanzDEU.info-sdb@dentsplysirona.com

- · Further information obtainable from: Research and Development
- 1.4 Emergency telephone number: +49-(0)7531-583-0 8:00 17:00 (GMT + 1:00)

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Skin Irrit. 2 H315 Causes skin irritation. Eve Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

propan-2-ol

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No P210

smoking.

P251 Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.

(Contd. on page 2)

Printing date 23.01.2023 Version number 6 (replaces version 5) Revision: 23.01.2023

Trade name: Fix Solvent Aerosol

· vPvB: Not applicable.

(Contd. of page 1)

### SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:				
	propan-2-ol	50 – 100%		
EINECS: 200-661-7	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336			
CAS: 106-97-8	butane, pure	10 – 25%		
EINECS: 203-448-7	Flam. Gas 1A, H220; Press. Gas (Comp.), H280			
	xylene (mix)	10 - 25%		
EINECS: 215-535-7	Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315			

· Additional information For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · General information Immediately remove any clothing soiled by the product.
- · After inhalation Supply fresh air; consult doctor in case of complaints.
- · After skin contact Immediately wash with water and soap and rinse thoroughly.
- · After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing If symptoms persist consult doctor.
- · Information for doctor No further relevant information available.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

## SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents

Water with full jet.

Water.

- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

(Contd. on page 3)

Printing date 23.01.2023 Version number 6 (replaces version 5)

Trade name: Fix Solvent Aerosol

(Contd. of page 2)

Revision: 23.01.2023

See Section 13 for disposal information.

### SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Observe normal care for working with chemicals.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.



Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · Handling Product is intended for dental use only.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep receptacle tightly sealed.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

	1		
· Ingredients with limit values that require monitoring at the workplace:			
CAS: 67-63-0 propan-2-ol			
WEL	Short-term value: 1250 mg/m³, 500 ppm		
	Long-term value: 999 mg/m³, 400 ppm		
CAS:	106-97-8 butane, pure		

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm

Carc (if more than 0.1% of buta-1.3-diene)

CAS: 1330-20-7 xylene (mix)

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

Regulatory information WEL: EH40/2020

Ingredients with biological limit values:

CAS: 1330-20-7 xylene (mix)

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift

Parameter: methyl hippuric acid

- Regulatory information BMGV: EH40/2011
- · Additional information: The lists valid during the making were used as basis.

(Contd. on page 4)

*Version number 6 (replaces version 5)* Printing date 23.01.2023 Revision: 23.01.2023

Trade name: Fix Solvent Aerosol

(Contd. of page 3)

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- · Respiratory protection: Not necessary if room is well-ventilated.
- · Hand protection



Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/

the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Tightly sealed goggles.

· **Body protection:** Protective work clothing.

#### SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Flammability

Aerosol · Physical state Colourless · Colour: Solvent-like · Odour: · Odour threshold: Not determined. · Melting point/freezing point: undetermined

· Boiling point or initial boiling point and boiling

range

· Lower and upper explosion limit

· Lower: ≥ 1.1 Vol % (CAS: 1330-20-7 xylene (mix)) · Upper: ≤ 13.4 Vol % (CAS: 67-63-0 propan-2-ol) · Flash point: ≥-60 °C (CAS: 106-97-8 butane, pure) · Ignition temperature: ≥ 365 °C (CAS: 106-97-8 butane, pure)

≥-0.5 °C (CAS: 106-97-8 butane, pure)

Not applicable.

Not applicable · Decomposition temperature: Not determined.

Not determined.  $\cdot pH$ 

(Contd. on page 5)

Printing date 23.01.2023 Version number 6 (replaces version 5) Revision: 23.01.2023

Trade name: Fix Solvent Aerosol

(Contd. of page 4)

· Viscosity:

· Kinematic viscosity
Not determined.
· dynamic:
Not determined.

Solubility

· Water: Not miscible or difficult to mix

· Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure at 20 °C: ≤ 2,100 hPa (CAS: 106-97-8 butane, pure)

Density and/or relative density

Density at 20 °C:
 Relative density
 Vapour density
 Not determined.
 Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

Important information on protection of health and

environment, and on safety.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Not determined.

· Solvent content:

· Organic solvents: 100.0 %
· Solids content: 0.0 %

· Change in condition

• Evaporation rate Not applicable.

· Information with regard to physical hazard classes

Explosives VoidFlammable gases Void

· Aerosols Extremely flammable aerosol. Pressurised container:

May burst if heated.

· Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void

· Substances and mixtures, which emit flammable

Substances and mixtures, which emit flammable gases in contact with water

Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals
Desensitised explosives
Void

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known

GB

Printing date 23.01.2023 Version number 6 (replaces version 5)

Trade name: Fix Solvent Aerosol

(Contd. of page 5)

Revision: 23.01.2023

## SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

· LD/LC50	· LD/LC50 values relevant for classification:				
ATE (Acu	ATE (Acute Toxicity Estimate)				
Dermal	LD50	11,333 mg/kg (rabbit)			
CAS: 67-6	63-0 propai	n-2-ol			
Oral	LD50	5,045 mg/kg (rat)			
Dermal	LD50	12,800 mg/kg (rab)			
CAS: 1330	0-20-7 xyle	nne (mix)			
Oral	LD50	4,300 mg/kg (rat)			
Dermal	LD50	1,700 mg/kg (rabbit)			
Inhalative	LC50/4 h	21.7 mg/l (rat)			

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- · STOT-single exposure May cause drowsiness or dizziness.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

CAS: 67-63-0 propan-2-ol

LC50/96h 1,400 mg/l (Fish acute toxicity study)

EC50/48h 13,299 mg/L (daphnia magna)

CAS: 1330-20-7 xylene (mix)

LC50/48h 8.5 mg/l (daphnia magna)

LC50/96h 15.7 mg/l (Fish acute toxicity study)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes: Do not allow product to reach ground water, water course or sewage system.

GR

Printing date 23.01.2023 Version number 6 (replaces version 5) Revision: 23.01.2023

Trade name: Fix Solvent Aerosol

(Contd. of page 6)

# SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

· 14.1 UN number or ID number	
· ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name	
· ADR	1950 AEROSOLS
· IMDG	AEROSOLS
· IATA	AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
· ADR	
· Class	2 5F Gases.
· Label	2.1
· Class	2.1 Gases.
· Label	2.1
· 14.4 Packing group	
· ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Warning: Gases.
· Hazard identification number (Kemler code):	
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of
	litre: Category A. For AEROSOLS with a capacity abo
	1 litre: Category B. For WASTE AEROSOLS: Category
	C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of
	litre:
	Segregation as for class 9. Stow "separated from" cla
	1 except for division 1.4.
	For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of cla
	2.

Printing date 23.01.2023 Version number 6 (replaces version 5) Revision: 23.01.2023

Trade name: Fix Solvent Aerosol

	(Contd. of page
	For WASTE AEROSOLS: Segregation as for the appropriate subdivision of clas 2.
· 14.7 Maritime transport in bulk according	g to IMO
instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· Transport category	2
Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	IL
· Excepted quantities (EQ)	Code: E0
· · ·	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

## SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The attached safety data sheet covers the dangers and measures to be taken when large quantities of material are released, for example due to accidents during transport or storage by the dealer.

For quantities of material typically used in clinical practice, information necessary for safe use and storage of the product is given in the DFU.

#### · Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

- · Department issuing SDS: Research & Development
- Contact: HotLine for urgent technical support: +49-7531-583-350
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 9)

Printing date 23.01.2023

Version number 6 (replaces version 5)

Trade name: Fix Solvent Aerosol

(Contd. of page 8)

Revision: 23.01.2023

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

\* \* Data compared to the previous version altered.