(amended by regulation (EU) Nr. 453/2010)

Date of issue: 23.04.2015Pro-Lux Spacer transparentDate of revision: 29.12.20Pro-Lux Spacer red transparent

Valid from: 29.12.20

Version: 4 Replaces version: 3 03-2200, 03-2210

Section 1: Identification of the substance/mixture and of the company

1.1 Product Identifier

Substance: Methacrylate
Index-no.: 607-035-00-6
EINECS: 201-297-1
CAS-no.: 80-62-6
REACH-registration no.: void

Other means or identification: not determined

1.2Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: SU 20 health care, light curing die spacer (dental labs).

Uses advised against: Should not be used outside a dental lab.

1.3 Details of the supplier of the safety data sheet

Supplier:

al dente Dentalprodukte GmbH

Street:

Borsigstr. 1

Address / zip-code / town:

D-38644 Goslar

Information contact:

+49 (0) 5321-80031

Phone / Fax / Email:

+49 (0)5321-80031 / +49 (0)5321-50881 / E-Mail: info@aldente.de

1.4 Emergency Telephone Number:

+49 (0) 171 8637790

Section 2: Hazards identification:

2.1 Classification of the substance or mixture:

Classification according to regulation (EC) no. 1272/2008 (CLP) Flammable liquids (chapter 2.6), category 2 (Flam. Liq. 2), H225, Skin irritation (chapter 3.2), category 2 (skin irrit. 2), H 315 Sensitisation of skin (chapter 3.4S), category 1 (skin sens), H317 May cause respiratory irritation (chapter 3.8R), category 3, (Stot Se 3), H 335 For the full text of the H-statements mentioned in this section, see section 16.

2.2 Label Elements

Labelling according to regulation (EC) no. 1272/2008 (CLP/GHS)

Hazard pictograms: GHS02, GHS07





Signal word: Danger (Flam.Liq. 2), Warning (Skin Irrit. 2), (Stot Se3), (Skin Sens1), Reduced labelling (≤125 ml) (according to exemptions from the packaging and labelling regulations according to EC-CLP-

(amended by regulation (EU) Nr. 453/2010)


Date of issue: 23.04.2015Pro-Lux Spacer transparentDate of revision: 29.12.20Pro-Lux Spacer red transparent

Valid from: 29.12.20

Version: 4 Replaces version: 3 03-2200, 03-2210

regulation) Signal word: danger hazard pictograms:





Hazardous component(s) for labelling:

Contains Methacrylate

Hazard statements:

H225: Highly flammable liquid H315: Causes skin irritation

H317: May cause an allergic skin reaction H335: May cause respiratory irritation

Precautionary statements:

P102: Keep out of reach of children.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray. P403 +P235: Store in a well-ventilated place. Keep cool.

P210: Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

Supplemental Hazard information (EU):

EUH066: Repeated exposure may cause skin dryness or cracking.

Full text of H- and EUH-phrases: see SECTION 16

2.3 Other Hazards:

No supplementary information available.

SECTION 3: Composition/information on ingredients

3.1 Substances

Principal component of the substance:

Substance name: Methacrylate Index-no.: 607-035-00-6 EINECS: 201-297-1

EINECS: 201-297-1 CAS-no.: 80-62-6

This substance does not meet the PBT or vPvB criteria according to the regulation (EC) no. 1907/2006, annex XIII.

Impurities, stabilizers:

Except for Methacrylate the spacer does not contain any other dangerous components.

3.2 Mixtures – not applicable

Description of the mixture:

EG-no.: CAS-no.: Index-Nno.: REACH-registration no.:

Content ration: %

Classification according to regulation (EC) no. 1272/2008 (CLP)

(Full text of H- and EUH-phrases: see SECTION 16)

Section 4: First aid measures

page: 2/9

(amended by regulation (EU) Nr. 453/2010)

Date of issue: 23.04.2015Pro-Lux Spacer transparentDate of revision: 29.12.20Pro-Lux Spacer red transparent

Valid from: 29.12.20

Version: 4 Replaces version: 3 03-2200, 03-2210

4.1 Description of first aid measures:

In general: take off contaminated clothing

Following inhalation:

In case of dizziness after inhalation of vapors, take the person concerned to fresh air.

Following skin contact:

Take off contaminated clothing. Wash affected skin thoroughly with water and soap. If irritation persists consult a doctor.

Following eye contact:

Rinse eyes with current water for at least 10 minutes. If eye irritation persists consult a doctor.

Following ingestion:

Rinse mouth and drink a lot of water – do not induce vomiting (aspiration hazard). If discomfort persist consult a doctor presenting this safety data sheet.

4.2 Most important symptoms and effects, both acute and delayed

Irritant effects, drowsiness, nausea, vomiting, headache, doziness.

4.3 Indication of any immediate medical attention and special treatment needed

Notes for the doctor: not determined Special treatment: not determined

Section 5: Firefighting measures

5.1 Extinguishing media

Suitable: dry powder, foam, sand

Unsuitable: water

5.2 Special hazards arising from the substance or mixture

Flammable. An incomplete combustion may result in toxic components within the flue gas. In case of fire a respiratory equipment working independently from its ambient environment is recommended for the fire fighters. Danger of flashback. Possibility of autopolymerisation.

5.3 Advice for fire-fighters

In case of fire a respiratory equipment working independently from its ambient environment is recommended for the fire fighters.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures For non-emergency personnel

Remove all sources of ignition immediately. Ensure good ventilation. Do not inhale fume or spray.

For emergency responders

Personal protective equipment:

respiratory equipment working independently from its ambient environment

6.2 Environmental precautions

Prevent the liquids from ingressing into surface water or drains.

6.3 Methods and material for containment and cleaning up

Wear safety equipment, absorb with liquid binding material (sand, universal binding material) and dispose of as hazardous material.

6.4 Reference to other sections

Dangerous combustion products: see section 5. Personal protective equipment: see section 8.

page: 3 / 9

(amended by regulation (EU) Nr. 453/2010)

Date of issue: 23.04.2015 Pro-Lux Spacer transparent Date of revision: 29.12.20 Pro-Lux Spacer red transparent

Valid from: 29.12.20

Version: 4 Replaces version: 3 03-2200, 03-2210

Section 7: Handling and storage

7.1 Precautions for safe handling

No particular measures are necessary when used properly.

Fire preventions:

Provide adequate ventilation. Keep away from sources of ignition – don't smoke!



Aerosol and dust generation preventions:

Not determined

Environmental precautions:

Prevent the liquids from ingressing into surface water or drains.

Advice on general occupational hygiene:

Follow the advice on general occupational hygiene, when dealing with chemicals, keep away from food, don't smoke.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Store under 30°C, tightly closed. Keep away from food. Don't store in direct sunlight.

Requirements for storage rooms and vessels

According to TRGS 510, annex 9, regulation for small quantities

Storage class: (LGK) (VCI) 3

7.3 Specific end uses

Sector specific quidelines: dental laboratories

Except for the applications mentioned in section 1.2 there are no other specific end applications provided.

Section 8: Exposure controls / personal protection

8.1 Control parameters

Occupational exposure limits

Substance: Methacrylate ; CAS-no. 80-62-6

Specification: TRGS 905/TRGS 900 exposure limits

Limit value type (country 400 m2/m³ (ppm)

of origin):

Peak limitation: Exceedance factor (ÜF) 2, category for short term values II

A risk of foetal damage is ceased to fear when observing the MAK / BAT values. Toxic to reproduction:

Not determined Source:

DNEL- and PNEC-values: not determined

8.2 Exposure controls

Appropriate engineering controls

Personal protective equipment

Eye / face protection

page: 4/9

(amended by regulation (EU) Nr. 453/2010)

Date of issue: 23.04.2015Pro-Lux Spacer transparentDate of revision: 29.12.20Pro-Lux Spacer red transparentValid from: 29.12.20

Version: 4 Replaces version: 3 03-2200, 03-2210



Wear tight fitting googles

Skin protection

Hand protection

The glove material has to be impermeable and resistant to the product.

Full contact:

Gloves made of butyl rubber. Layer thickness: ≥ 0.7 mm Penetration time: ≥ 60 min



Splash contact:

Gloves made of nitrile rubber Layer thickness: 0,40 mm Penetration time: < 120 min.

Body protection

Wear adequate working clothes.

Respiratory protection

Generally there are no specific measures to be taken. In case of release of a more important quantity (drained off bottle) provide for sufficient ventilation.

Thermal hazards

Not applicable if not stored over 45°C for a longer space of time.

Environmental exposure controls

Not determined

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties:

Physical state:

Aggregate state: liquid

colour: transparent / red transparent Odour: specific according to product Odour threshould: not determined

pH-value: not determined

Melting point / freezing point : Not determined

Initial boiling point/boiling range : Starting from 98°C

Flash point: 10 °C (DIN 51755) Evaporation rate : not determined Flammability: not determined

Upper/lower explosive limits: no data available

Vapour pressure : not determined Vapour density: not determined Relative density: not determined

page: 5 / 9

(amended by regulation (EU) Nr. 453/2010)

Date of issue: 23.04.2015Pro-Lux Spacer transparentDate of revision: 29.12.20Pro-Lux Spacer red transparent

Valid from: 29.12.20

Version: 4 Replaces version: 3 03-2200, 03-2210

Solubility: slightly mixable in water Partition coefficient: not determined n-octanol/water: not determined Auto-ignition temperature: 434°C

Decomposition temperature: not determined

Viscosity: not determined

explosive properties: considered as being non-explosive

Oxidising properties: not determined

Other information

9.2

Physical hazards

Explosives There are no further data available

Section 10: Stability and reactivity

10.1 Reactivity:

Risk of ignition

10.2 Chemical stability:

Under standard ambient conditions the material is chemically stable.

10.3 Possibility of hazardous reactions:

Not determined

10.4 Conditions to avoid:

Storing for a longer space of time over 45°C, direct sunlight (possibility of autopolymerisation).

10.5 Incompatible materials: oxidizing agents

10.6 Hazardous decomposition products:

When storing at room temperature: none.

Section 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Oral LD50 7.872 mg/kg (rat) (TOXNET) Dermal LS50 >5000 mg/kg (rabbit) (TOXNET)

Skin irritation

Absorbtion of acute toxics exclusively through skin contact is considered as being quite unlikely. Can be irritating to skin and mucous membranes upon direct contact.

Repeated or prolonged exposure may cause skin irritation and dermatitis due to degreasing properties of the product (EUH066)

Eye irritation

Result rabbit: weak eye irritation effect

After inhalation: irritation of mucous membranes, coughing, shortness of breath

Sensitisation of skin: sensitisation possible after skin contact.

Germ cell mutagenicity

No details available.

page: 6 / 9

(amended by regulation (EU) Nr. 453/2010)

Date of issue: 23.04.2015Pro-Lux Spacer transparentDate of revision: 29.12.20Pro-Lux Spacer red transparent

Valid from: 29.12.20

Version: 4 Replaces version: 3 03-2200, 03-2210

Carcinogenicity

No details available.

Reproductive toxicity

No known significant effects or critical hazards.

Specific target organ toxicity (single exposure): may cause respiratory irritation

Specific target organ toxicity (repeated exposure): The substance is not classified on organ toxicity on repeated exposure (see single exposure).

Symptoms related to the physical, chemical and toxicological characteristics:

In case of ingestion: possible digestive problems
In case of skin contact: may cause irritation of skin

In case of inhalation: headache, dizziness, cough, irritation of the respiratory system

In case of eye contact: slight irritation possible

Section 12: Ecological information

12.1 Toxicity

Aquatic toxicity / fish toxicity:

This product is slightly hazardous to water. The risk arising from a small container (20 ml) can be neglected.

12.2 Persistence and degradability

According to 1272/2008/CE: not to be considered as water hazardous.

Easily biodegradable.

Theoretical oxigen demand: 1,918 mg/mg Theoretical carbon dioxide: 2,198 mg/mg

12.3 Bioaccumulative potential

Not significantly accumulative. n-Octanol/Water (log KOW) 1,38

12.4 Mobility in soil

No information available

12.5 Results of PBT- and vPvB assessment

Not applicable

12.6 Other adverse effects

No further relevant information available.

Section 13: Disposal considerations

13.1 Waste treatment methods

Contaminated packaging disposal

Containers are to be treated as the product itself. 150110 (AVV)

Waste codes / waste designations according to EWC / AVV:

160506 (AVV)

The product is to be considered as special waste and has to be disposed of according to the national and regional regulations (varnishes).

page: 7 / 9

(amended by regulation (EU) Nr. 453/2010)

Date of issue: 23.04.2015Pro-Lux Spacer transparentDate of revision: 29.12.20Pro-Lux Spacer red transparent

Valid from: 29.12.20

Version: 4 Replaces version: 3 03-2200, 03-2210

Special precautions: not applicable

Other relevant provisions for waste treatment national or EC

Waste directive 2008/98/EC has to be observed.

Section 14: Transport information

14.1 UN-no. 1247

14.2UN proper shipping name

ADR/RID: METHYLMETHACRYLATE, MONOMER, stabilized

IMDG-Code / ICAO-TI / IATA-DGR: E2

14.3 Transport hazard class(es) / hazard labels: 3

14.4 Packing group: II

14.5 Environmental hazards

Environmentally hazardous substance marking

ADR/RID / IMDG-Code / ICAO-TI / IATA-DGR: yes / **XXXXX no** Marine Pollutant: yes / **XXX no** slightly hazardous to waters

EMS-Code: F-E,S-D

14.6 Special precautions for user

Requirements for dangerous goods (ADR) are also applicable inside the premises.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category (X, Y or Z): not applicable, package size: 20 ml Type of ship (1, 2 or 3): not applicable, package size: 20 ml

No bulk transports!

Section 15: Regulatory information

15.1Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-regulations, e.g.:

Directive / EC no. 2037/2000 (substances that deplete the ozone layer): not applicable

Directive / EC no. 850/2004 (persistent organic pollutants): not applicable

Directive / EC no.. 689/2008 (export and import of dangerous chemicals): not applicable

Directive / EC no. 648/2004 (detergent regulation): not applicable

(amended by regulation (EU) Nr. 453/2010)

Date of issue: 23.04.2015Pro-Lux Spacer transparentDate of revision: 29.12.20Pro-Lux Spacer red transparent

Valid from: 29.12.20

Version: 4 Replaces version: 3 03-2200, 03-2210

National regulations, e.g.:

Water hazard class: 1 (slightly hazardous to water) Solvents regulation (31. BImSchV): not applicable Accidents Ordinance (12. BImSchV): not applicable

Technical instructions on Air Quality Control (TA-Luft): not applicable

Other relevant regulations

Not applicable

15.2 Chemical safety assessment

No chemical safety assessment has been performed on this substance.

Section 16: Other information

Indication of changes

Adaption to the classification and labelling according to directive (EC) no. 1272/2008 Section 1: Emergency phone number.

Abbreviations and acronyms

n.a. Not applicable

Key literature references and sources for data

Gestis substance data base - http://gestis.itrust.de/

Federal Agency for Industrial Health and Safety - www.baua.de

Classification for mixtures and used evaluation method according to regulation (EC) 1207/2008 [CLP]:

Relevant R-, H- and EUH-phrases (number and full text):

Hazard statements:

H225: Highly flammable liquid and vapour.
H319: Causes serious eye irritation.
H336: May cause drowsiness and dizziness

Precautionary statements:

P210: Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P233: Keep container tightly closed. P102: Keep out of reach of children.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lense

present and easy to do. Continue rinsing.

Supplemental Hazard information (EU):

EUH066: Repeated exposure may cause skin dryness or cracking.

Training advice

Provide adequate information, instruction and training for operators / technicians using this product.

Further Information

This information is based on our present state of knowledge. It should therefore not be construed as guaranteeing specific properties of the products described or their suitability for a particular application. We do not take any responsibility for possible sources of errors or sufficiency of this document. The user of the product accepts the sole responsibility to adhere to all herein mentioned regulations. It is the user's obligation to read this document carefully.