

according to Regulation (EC) No 1907/2006

trayloc® A

Revision date: 01.02.2024 Product code: 10100 Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

travloc® A

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: DETAX GmbH
Street: Carl-Zeiss-Straße 4
Place: D-76275 Ettlingen
Telephone: +49 7243/510-0

T mail: 1243/310-0

E-mail: post@detax.com Internet: www.detax.com

Responsible Department: This number is only obtainable during office hours

(Monday - Thursday 8.00 a.m. - 5.00 p.m., Friday 8.00 a.m. - 4.00 p.m.)

Telefax: +49 7243/510-100

1.4. Emergency telephone +1-800-424-9300 (CHEMTREC worldwide)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

@000000030323 ethyl acetate

Signal word: Danger

Pictograms:





Hazard statements

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P235 Keep cool.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder to



according to Regulation (EC) No 1907/2006

trayloc® A

Revision date: 01.02.2024 Product code: 10100 Page 2 of 9

extinguish.

P501

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity	
	EC No	Index No	REACH No		
	Classification (Regulation (EC) No	1272/2008)			
67-63-0	"propan-2-ol; isopropyl alcohol; isopropanol"				
	200-661-7	603-117-00-0			
	Flam. Liq. 2, Eye Irrit. 2, STOT SE	3; H225 H319 H336			
141-78-6	ethyl acetate			40 - < 60 %	
	205-500-4	607-022-00-5	01-2119475103-46		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits. M-factors and ATE

CAS No	EC No	Chemical name	Quantity					
	Specific Conc.	Specific Conc. Limits, M-factors and ATE						
67-63-0	200-661-7	"propan-2-ol; isopropyl alcohol; isopropanol"	40 - < 60 %					
	dermal: LD50	dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg						
141-78-6	205-500-4	ethyl acetate	40 - < 60 %					
	inhalation: LC50 = >29,3 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg							

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

DETAX GmbH



Safety Data Sheet

according to Regulation (EC) No 1907/2006

trayloc® A

Revision date: 01.02.2024 Product code: 10100 Page 3 of 9

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder.

5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe qas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



according to Regulation (EC) No 1907/2006

trayloc® A

Revision date: 01.02.2024 Product code: 10100 Page 4 of 9

Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m³	fib/cm³	Category	Origin
141-78-6	Ethyl acetate	200	734		TWA (8 h)	
		400	1468		STEL (15 min)	

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Butyl caoutchouc (butyl rubber)

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid: Colour: blue

Test method

Melting point/freezing point: not determined

Boiling point or initial boiling point and 70 °C DIN 51356

boiling range:

Flammability: not applicable

not applicable

Lower explosion limits: 2 vol. % Upper explosion limits: 13 vol. %

Flash point: -3 °C DIN 51755

Auto-ignition temperature: 450 °C DIN 51794

Decomposition temperature: not determined pH-Value: not determined Water solubility: partially miscible

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined Vapour pressure: 70 hPa

(at 20 °C)

Vapour pressure: 310 hPa

(at 50 °C)

Density (at 20 °C): 0,84 g/cm³ DIN 51757

Relative vapour density: not determined



according to Regulation (EC) No 1907/2006

trayloc® A

Revision date: 01.02.2024 Product code: 10100 Page 5 of 9

9.2. Other information

Information with regard to physical hazard classes

Self-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties Not oxidizing.

Other safety characteristics

Evaporation rate: not determined

Solid content: not determined

Viscosity / dynamic: 1 mPa·s

(at 23 °C)

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name	Chemical name							
	Exposure route	Dose		Species	Source	Method			
67-63-0	"propan-2-ol; isopropyl al	cohol; isopro	panol"						
	oral	LD50 mg/kg	>2000	Rat					
	dermal	LD50 mg/kg	>2000	Rabbit					
141-78-6	ethyl acetate								
	oral	LD50 mg/kg	>2000	Rat					
	dermal	LD50 mg/kg	>2000	Rabbit					
	inhalation (4 h) vapour	LC50 mg/l	>29,3	Rat					



according to Regulation (EC) No 1907/2006

trayloc® A

Revision date: 01.02.2024 Product code: 10100 Page 6 of 9

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. ("propan-2-ol; isopropyl alcohol; isopropanol"; ethyl acetate)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d] Species		Source	Method	
67-63-0	"propan-2-ol; isopropyl alcohol; isopropanol"							
	Acute algae toxicity	ErC50 >100 mg/l		72 h	Scenedesmus subspicatus			
	Acute crustacea toxicity	EC50 mg/l	>100		Daphnia magna (Big water flea)			
141-78-6	ethyl acetate							
	Acute fish toxicity	LC50 mg/l	>100		Salmo trutta fario (L) (Freshwater trout)	OECD 203		
	Acute algae toxicity	ErC50 mg/l	>100	72 h	Desmodesmus subspicatus	OECD 201		
	Acute crustacea toxicity	EC50 mg/l	>100	48 h	Daphnia magna (Big water flea)			

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name	Chemical name						
	Method	Value		d	Source			
	Evaluation							
67-63-0	"propan-2-ol; isopropyl alcohol; isopropanol"							
	Activated sludge	53%		5				
	Readily biodegradable (according to OECD criteria).							
141-78-6	ethyl acetate							
	OECD 301D/ EEC 92/69/V, C.4-E	>70%		28				

12.3. Bioaccumulative potential

The product has not been tested.



according to Regulation (EC) No 1907/2006

trayloc® ARevision date: 01.02.2024Product code: 10100Page 7 of 9

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	"propan-2-ol; isopropyl alcohol; isopropanol"	<=4
141-78-6	ethyl acetate	0,68

BCF

CAS No	Chemical name	BCF	Species	Source
141-78-6	ethyl acetate	30	Leuciscus idus (golden orfe)	

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN nı</u>	<u>imber or ID n</u>	<u>umbe</u> i	<u>r:</u>	UN 1866
14.2. UN pı	oper shipping	<u>e:</u>	Resin solution	
				•

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Classification code:F1Limited quantity:5 L/ 30 kgTransport category:2Hazard No:33Tunnel restriction code:D/E

Marine transport (IMDG)

14.1. UN number or ID number:UN 186614.2. UN proper shipping name:Resin solution

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Marine pollutant:-Special Provisions:-

Limited quantity: 5 L/ 30 kg EmS: 5 L/ 30 kg



according to Regulation (EC) No 1907/2006

trayloc® A

Revision date: 01.02.2024 Product code: 10100 Page 8 of 9

Other applicable information (marine transport)

Flash point: -3°C c.c.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1866
14.2. UN proper shipping name: Resin solution

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3

Limited quantity Passenger: 1 L/ 30 kg Passenger LQ: Y341

IATA-packing instructions - Passenger:353IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:364IATA-max. quantity - Cargo:60 L

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50% LD50: Lethal dose, 50%

LD50: Lethal dose, 50% Flam. Liq: Flammable liquid Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.





according to Regulation (EC) No 1907/2006

trayloc® A

Revision date: 01.02.2024 Product code: 10100 Page 9 of 9

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Gewerblich	-	-	-	-	-	-	-	2

LCS: Life cycle stages PC: Product categories

ERC: Environmental release categories

TF: Technical functions

SU: Sectors of use PROC: Process categories

AC: Article categories

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)