## Enjoy maximum power with innovative KaVo comfort.

MASTERmatic LUX speed increasing contra angle

3-port spray - push-button chuck - ceramic ball bearing -

head 20 % smaller than GENTLEpower LUX 25 LP -

MASTERmatic LUX reducing shank 7.4:1

Maximum treatment flexibility and options provided by

handpiece 1:5 transmission ratio

very low noise level (55 dB(A))

M25 L | Mat. No. 1.009.3630

M29 L | Mat. No. 1.009.3580

- 1. Best treatment quality.
- 2. Maximum treatment comfort.
- 3. Highest patient satisfaction.

Handpieces and contra-angle handpieces

MASTERmatic™ series 🗓 📉 Features of the MASTERmatic series: Plasmatec coating for perfect grip Replaceable spray microfilter Glass rod light conductor Internally guided, separate cooling media M25 L/M05 L: More space due to the 100°/19° head/knee angle combination and smaller heads • 24 months warranty for MASTERmatic  $^{\text{TM}}$ and INTRA™ heads \* except M10 L



M05 L | Mat. No. 1.009.3640 INTRA™ Heads



Push-button chuck - for FG-burs Ø 1.6 mm



L68 | Mat. No. 1.008.1833

Push-button chuck - for contra-angle handpiece burs and root canal filler instruments max. speed: 2,000 rpm L62 | Mat. No. 1.008.1830





Round bur, size 2 and U-inverted cone bur size 0 for microsurgery - max. speed: 20,000 rpm L22 | Mat. No. 1.008.1835



Push-button chuck - for manual root canal nstruments with grip diameter 3.5–4.0 mm (9/64-5/32 in) - reciprocating rotation through 60° - max. speed: 3,000 rpm 13 | Mat. No. 1.008.1822



struments – suitable for endo function of the ESTETICA E70/E80 Vision in combination with MASTERmatic M20 L I 68 B | Mat. No. 1.008.1834

MASTERmatic LUX shank 1:1

14 exchangeable heads

M20 L | Mat. No. 1.009.3620

M10 L | Mat. No. 1.009.3570

 ${\it Maximum\ treatment\ flexibility\ and\ options\ provided\ by}$ 

For both handpiece and contra-angle handpiece burs

Push-button chuck - ball bearings - for

L66 B | Mat. No. 1.008.1831

speed: 20,000 rpm

L61 G | Mat. No. 1.008.1828

contra-angle handpiece burs and root canal

Files rotate freely - with buffered 0.8 mm

instruments - suitable for endo function of the ESTETICA E70/E80 Vision in combination with



Push-button chuck - for manual root canal instruments with grip diameter of 3.5 - 4.0 mm - lift motion 0.4 mm - instrument receptacle rotates 360° - max. speed: 3,000 rpm 13 Y | Mat No 1 008 1823

Push-button chuck - for root canal instrument and polishing attachments with 2.35 mm shaft diameter (latch) - reciprocating rotation through 60° - max. speed: 3,000 rpm L53 | Mat. No. 1.008.1826

## Rely on advanced KaVo performance.

- 1. Maximum longevity.
- 2. Efficient operations.
- 3. Reliable features.

Handpieces and contra-angle handpieces

Features of the EXPERTmatic series • KaVo EXPERTgrip for better grip Internally guided, separate cooling media

E25 L/ E20 L/ E15L: Glass rod light conductor

COMFORTdrive contra-angle handpiece EXPERTmatic LUX speed increasing contra-angle handpiece 1:5 High-speed contra-angle handpiece - very light-weight and handy – integrated brushless motor – glass rod light 3-port spray - push-button chuck - ceramic ball bearings conductor – ceramic ball bearings – replaceable spray microfilter - 3-port-spray - for direct connection only E25 L | Mat. No. 1.007.5550

handpiece with 1:5 transmission ratio 3-port spray - push-button chuck - ceramic ball bearings replaceable spray microfilter E25 C (without light) | Mat. No. 1.007.5551 Push-button chuck - for miniature contra-angle handpiece burs (16 mm (5/8 in)) - max. speed:

L52 | Mat. No. 1.008.1825

With 36 separate locking positions for locking

files - with buffered 0.8 mm (1/32 in) stroke

for files by Intensiv - max. speed: 20,000 rpm

L61 R | Mat. No. 1.008.1829

MASTERmatic LUX reducing shank 2.7:1

14 exchangeable heads

24 months warranty

M07 L | Mat. No. 1.009.3610

COMFORTdrive™

Maximum treatment flexibility and options provided by





Push-button chuck - for contra-angle handpiece burs -E20 L | Mat. No. 1.007.5540



E20 C (without light) | Mat. No. 1.007.5541



handpiece 5.4:1 Push-button chuck – for contra-angle handpiece burs debris deflector disc and reinforced chuck system

Push-button chuck - for contra-angle handpiece burs debris deflector disc and reinforced chuck system E15 C (without light) | Mat. No. 1.007.5531



Prep control head with 36 locking positions for polishing inserts - with buffered 0.8 mm (1/32 in) stroke for files by Intensiv E61 C (without light) | Mat. No. 1.008.4999

## Start safe with affordable KaVo quality.

- 1. Made in Germany.
- 2. Premium materials.
- 3. Entry level price for the world of KaVo.

Handpieces and contra-angle handpieces

SMARTmatic™ series 🗓 📉 Features of the SMARTmatic series: Smaller head · Ceramic sliders within the clamping system • Extremely precise ball bearings Lightweight

· 12 months warrants



For burs with shaft Ø 2.35 mm - Internal spray transmission the Sprayclip - max. speed: 40,000 rpm S20 S | Mat. No. 1.011.6752 Also available without spra S20 | Mat. No. 1.011.6750

For endodontic files with shaft Ø 2.35 mm - max, speed: 40,000 rpm S81 | Mat. No. 1.011.6780





S31 | Mat.No. 1.011.6760



S33 | Mat. No. 1.011.6800

Doriot - max, speed: 20,000 rpm - for disposable prophylaxis angles S19 | Mat. No. 1.011.6740

SMARTmatic S10 S 1:1 with external spray

contra-angle handpiece drills

S10 S | Mat. No. 1.011.6732

S10 | Mat. No. 1.011.6730

Also available without spray

For burs with shaft Ø 2.35 mm - Internal spray trans

to the Sprayclip - max. speed: 40,000 rpm - for straight and



SMARTmatic S53 / Prophy, Endo 8:1 / 70° oscillating rotation direction For burs with shaft Ø 2.35 mm - max. speed: 20,000 rpm usable with polishing and root canal instruments S53 | Mat. No. 1.011.6810

Electric Motors / Air Motors / ELECTROmatic



Turbines [135°C] MASTERtorque™ series Features of the MASTERtorque series: · Direct Stop Technology DST: Bur stops in one second, no suck-back of aerosols Plasmatec coating for perfect grip Replaceable spray microfilte Chuck retention force up to 32 N Carbide guiding bush Ceramic ball bearing Glass rod light conductor Perfect sight and good access: small

head and 100°/19° head/ knee angle

• 24 months warranty



M9000 Lanthracite | Mat. No. 1.007.7100

MASTERtorque Mini LUX Turbine

for standard and miniature burs M8700 L | Mat. No. 3.001.0000 M8700 LS\* | Mat. No. 3.001.0600

Extra small head: head height 12.1 mm - low noise level up to 59 dB(A) - maximum power 30 Watt - 3-port spray

 $^{\star} \ \ \text{This instrument fits a non KaVo coupling system (LS = KaVo \ turbine \ fits \ to \ Sirona \ Click\&Go-coupling)}$ Maximum power data are measured at max. pressure settings for MULTIflex versions.

## Turbines III EXPERTtorque™ series

Features of the EXPERTtorque series: Replaceable spray microfilter

 Push-button chuck · Chuck retention force up to 30 N Carbide guiding bush Ceramic ball bearing Perfect sight: Small head and 100°/19° head/knee angle combination • 18 months warranty



height 13.6 mm - noise level up to 62 dB(A) E680 L | Mat. No. 1.006.8700 E680 LS\* | Mat. No. 1.006.4600 E680 LN\* | Mat. No. 1.006.4700

\* This instrument fits a non KaVo coupling system (LS = KaVo turbine fits to Sirona Click&Go- coupling, LN = KaVo turbine fits to NSK FlexQuick- coupling) Maximum power data are measured at max. pressure settings for MULTIflex versions.

62 dB(A)

EXPERTtorque Turbine

Maximum power 29 Watt - 4-port spray

head height 13.6 mm - noise level up to

E680 C (without light) | Mat. No. 1.006.9000

ELECTROmatic™ - The conversion kit from air to electrics

65 dB(A)

E677 L | Mat. No. 1.007.3600

E677 LN\* | Mat. No. 1.006.0100

Turbines Institution

SMARTtorque™ series **EXPERTtorque Mini LUX Turbine** SMARTtorque LUX Turbine Extra small head: head height 12.2 mm -Standard Head - Glass rod light conductor - 26 Watt Power ceramic bearings - made in Germany - push-button chuck three-port spray - glass rod light conductor maximum power 27 Watt - noise level up to four-port spray S619 L | Mat. No. 1.008.1641

> Miniature head - 22 Watt Power - ceramic bearings - made in Germany - glass rod light conductor - push-button chuck single-port spray S615 L | Mat. No. 1.008.1643

S619 C (without light) | Mat. No. 1.008.1642



S605 C (without light) - 4-hole standard connector - 22 Watt Mat. No. 1.008.1645

Maximum power data are measured at max. pressure settings.

Power - Midwest

Mat. No. 1.008.1644

MULTIflex™ Couplings



Prophylaxis and Minimally invasive applications

tions - no suck-back due to integrated anti-retraction w

rsed for subgingival treatments with the RODHYflex – removes biofilm in periodonta

cleaning
Perio Kit | Mat. No. 1.009.3731
Refill Set | Mat. No. 1.010.0287
PROPHYflex 4 Perio Kit | Mat. No. 1.011.9403







Prophylaxis and Minimally invasive applications

For all applications ranging from prophylaxis to surgery – 50 different tips –

ncludes torque wrench – SONICflex Set includes scaler tips no. 5/6/7 –

2003 L: glass rod light conductor - 12 months warranty

SONICflex LUX Set 2003 L | Mat. No. 1.000.8333

 ${\sf SONICflex\ LUX\ handpiece\ 2003\ L\ |\ Mat.\ No.\ 1.000.4243}$ 

SONICflex Set 2003 (without light) | Mat. No. 1.000.8334 SONICflex handpiece 2003 (without light) | Mat. No. 1.000.4246

frequency: 6,000 Hz - 3 adjustable power levels - direction of motion: circular -





SONICflex™ 2000 N

12 months warranty

2000 N | Mat. No. 0.5710.5020

frequency: 6,000 Hz - amplitude: 160µm - direction

of movement: circular - internal water cooling -

suitable for MULTIflex coupling - includes torque

wrench and SONICflex scaler tip no. 5 "Universal"

SONICflex™ 2008 quick

Prophylaxis and Minimally invasive applications

For all invasive applications ranging from prophylaxis to surgery-more than 50 different tips-rapid tip switch-frequency: 6,000 Hz-more than 50 different tips-rapid tips-rapid3 adjustable power levels - 2008 L/LS: glass rod light conductor - for KaVo or Sirona couplings - direction of motion: circular includes torque wrench - SONICflex quick Set includes scaler tips no. 5A/6A/7A - 24 months warranty SONICflex quick handpiece 2008 L | Mat. No. 1.005.9310 SONICflex quick Set 2008 L | Mat. No. 1.007.1604 SONICflex quick handpiece 2008 LS\* | Mat. No. 1.007.0540  $SONIC flex\ quick\ Set\ 2008\ (without\ light)\ |\ Mat.\ No.\ 1.007.1606 \\ SONIC flex\ quick\ hand piece\ 2008\ (without\ light)\ |\ Mat.\ No.\ 1.005.9311 \\ No.\ 1.005.9311$ \* This instrument fits a non KaVo coupling system (LS = KaVo instrument fits to Sirona Click&Go-coupling)



smooth - tastaless - alvoine nowder



SONICflex™ 2003













Surgery portfolio



EXPERTgrip - for straight burs with 44.5 mm (2 3/4 in) standard length - can also be used for contra-angle handpiece burs - external cooling connection -12 months warranty

INTRA LUX S600 LED | Mat. No. 1.008.8000



INTRA LUX reducing contra-angle handpiece 27:1 Glass rod light conductor - head and shank can be easily dismantled - head with internal cooling system (according to Kirschner and Meyer) - external cooling connection reinforced gearboxes for higher torques - automatic recognition by motor SL 550 - 12 months warranty



Reduction ratio 20:1 - Hexagon chuck system for a long

service life and a max. torque of 80 Ncm - optimized clamping system - removable head, easy to clean -EXPERTgrip - small head with internal cooling system - external cooling connection - optimised toothing at the head and improved ball bearings – 12 months S201 XL Pro (with hexagon + light) I Mat. No. 1.013.7541

CL 3-09 | Mat. No. 1.002.3693

CL 3 | Mat. No. 1.001.8993

Surgery reducing head INTRA LUX 3:1

Surgery reducing shank INTRA LUX 9:1

consisting of:



S201 L Pro (with light) I Mat. No. 1.013.7540

Glass rod light conductor - for straight burs with 44.5 mm (2.3/4 in) standard length - external cooling connection increased bur clamping force – automatic recognition by motor SL 550 – 12 months warranty CL 10 | Mat. No. 1.002.0911



range: 0 - 40,000 rpm, motor and motor cable: autoclavable &

disinfectable) - 12 months warranty

EXPERTSurg \$600 | FD | Mat. No. 1.008.3500

INTRA Surgical handpiece 1:1 For straight burs with 44.5 mm (2 3/4 in) standard length external cooling connection - easy to dismantle - reinforced chuck system – 12 months warranty 3610 N1 | Mat. No. 0.524.5600



For straight burs with 62.5 mm (215/32 in) special length external cooling connection - easy to dismantle - reinforced 3610 N2 | Mat. No. 0.524.5610

For straight burs with 70 mm (2 3/4 in) special length external cooling connection - easy to dismantle - reinforced chuck system – 12 months warranty 3610 N3 | Mat. No. 0.524.5620







S11 L (with light) | Mat. No. 1.009.1010

Special Instruments

Hygiene and Care











KaVo Dental GmbH | Bismarckring 39 | 88400 Biberach | Deutschland